








































Analogue Comparison Chart

Panasonic

				 New					
	WV-CW900 Series <small>WV-CW970/960 WV-CW974/964</small>	WV-CS950 Series <small>WV-CS950 WV-CS954</small>	WV-CS570 Series <small>WV-CS570 WV-CS574</small>	WV-CW500 <small>WV-CW500 WV-CW504</small>	WV-CW480 Series <small>WV-CW480 WV-CW484</small>	WV-CW240 Series <small>WV-CW240 WV-CW244</small>	WV-CF284/294 <small>WV-CF284 WV-CF294</small>	WV-CF324	WV-CF102
Fully Functional	✓	✓	✓						
Image Sensor									
Black & White									
IR Filter Shift	✓	✓		✓	✓				
Image Features	SDIII <small>Super Dynamic</small>	SDIII <small>Super Dynamic</small>		SD5 <small>Super Dynamic</small>	SDIII <small>Super Dynamic</small>		ABS	ABS	ABS
Back Focus						Manual	Manual 		Manual
Min. Illumination (Col) Lux	0.5 @ F1.4	0.5 @ F1.4	1.0 @ F1.6	0.3 lux	0.6 @ F1.4	1.0 @ F1.4	0.9	0.9 @ F1.3	1.2 @ F2.0
Min. Illumination (BW) Lux	0.04 @ F1.4	0.04 @ F1.4		0.04 lux	0.08 @ F1.4				
External Protection	IP66 <small>standard</small> 				IP66 <small>standard</small> 	IP66 <small>standard</small> 			
Optical Zoom	30x <small>OPTICAL ZOOM</small>	30x <small>OPTICAL ZOOM</small>	22x <small>OPTICAL ZOOM</small>	2x <small>OPTICAL ZOOM</small>	3.6x <small>OPTICAL ZOOM</small>	2x <small>OPTICAL ZOOM</small>	2x <small>OPTICAL ZOOM</small> 3.6x <small>OPTICAL ZOOM</small>	3.6x <small>OPTICAL ZOOM</small>	
Focal Length	3.8 - 114 mm	3.8 - 114 mm	3.79 - 83.4 mm	3.8 - 8 mm	3.8 - 8 mm	3.8 - 8 mm	2.8 - 6 mm 2.8 - 10 mm	2.8 - 10 mm	
Pan Range				± 170°	± 160°	± 175°	+180° ~ -140°	+180° ~ -140°	+180° ~ -140°
Tilt Range	-5° ~ 185°	-5° ~ 185°	-5° ~ 185°	± 75°	± 75°	± 75°	± 75°	± 75°	± 75°
Presets	256	256	32						
Input / Output	4 / 2	4 / 2	4 / 2						
Source (V AC)	220 - 240 24	220 - 240 24	220 - 240 24	220 - 240 24	220 - 240 24	220 - 240 24	24	24	12 V DC
Consumption	90 W 77 W	13 W 13 W	15 W 13 W	5.1 W 3.4 W	7 W 4.1 W	4.1 W 3 W	2.7 W	2.7 W	180 mA

*Information correct at time of printing. - Weights and dimensions are approximate. - Specifications are subject to change without notice.